

introduction

October 31, 2007

Contents

1	Introduction	1
2	Features	1
3	ParenScript Tutorial	4
4	Setting up the ParenScript environment	4
5	A simple embedded example	4
6	Adding an inline ParenScript	5
7	Generating a JavaScript file	6
8	A ParenScript slideshow	8
9	Customizing the slideshow	12
10	ParenScript Language Reference	14
11	Statements and Expressions	14
12	Symbol conversion	15
12.1	Reserved Keywords	15
13	Literal values	16
13.1	Number literals	16
13.2	String literals	16
13.3	Array literals	16
13.4	Object literals	17
13.5	Regular Expression literals	18
13.6	Literal symbols	18
14	Variables	18
15	Function calls and method calls	19
16	Operator Expressions	19

17	Body forms	20
18	Function Definition	21
19	Assignment	21
20	Single argument statements	22
21	Single argument expression	22
22	Conditional Statements	23
23	Variable declaration	24
24	Iteration constructs	25
25	The 'CASE' statement	26
26	The 'WITH' statement	27
27	The 'TRY' statement	27
28	The HTML Generator	28
29	Macrology	29
30	The ParenScript namespace system	30
31	Identifier obfuscation	31
32	The ParenScript Compiler	31

1 Introduction

ParenScript is a simple language that looks a lot like Lisp, but actually is JavaScript in disguise. Actually, it is JavaScript embedded in a host Lisp. This way, JavaScript programs can be seamlessly integrated in a Lisp web application. The programmer doesn't have to resort to a different syntax, and JavaScript code can easily be generated without having to resort to complicated string generation or `FORMAT` expressions.

An example is worth more than a thousand words. The following Lisp expression is a call to the ParenScript "compiler". The ParenScript "compiler" transforms the expression in ParenScript into an equivalent, human-readable expression in JavaScript.

```
(ps
  (defun foobar (a b)
    (return (+ a b))))
```

The resulting javascript is:

```
"
function foobar(a, b) {
  return a + b;
}
"
```

Great care has been given to the indentation and overall readability of the generated JavaScript code.

2 Features

ParenScript supports all the statements and expressions defined by the EcmaScript 262 standard. Lisp symbols are converted to camelcase, javascript-compliant syntax. This idea is taken from Linj by Antonio Menezes Leitao. Here are a few examples of Lisp symbol to JavaScript name conversion:

```
(js-to-string 'foobar)      => "foobar"
(js-to-string 'foo-bar)    => "fooBar"
(js-to-string 'foo-b-@-r)  => "fooBAtR"
(js-to-string 'foo-b@r)    => "fooBatr"
(js-to-string '*array)     => "Array"
(js-to-string '*math.floor) => "Math.floor"
```

It also supports additional iteration constructs, relieving the programmer of the burden of iterating over arrays. `for` loops can be written using the customary `DO` syntax.

```
(ps
  (do ((i 0 (incf i))
      (j (aref arr i) (aref arr i)))
      ((>= i 10))
      (alert (+ "i is " i " and j is " j))))

; compiles to
"
for (var i = 0, j = arr[i]; i < 10; i = ++i, j = arr[i]) {
  alert('i is ' + i + ' and j is ' + j);
}
"
```

ParenScript uses the Lisp reader, allowing for reader macros. It also comes with its own macro environment, allowing host Lisp macros and ParenScript macros to coexist without interfering with each other. For example, the `1+` construct is implemented using a ParenScript macro:

```
(defpsmacro 1+ (form)
  '(+ ,form 1))
```

ParenScript allows the creation of JavaScript objects in a Lispy way, using keyword arguments.

```
(ps
  (create :foo "foo")
```

```

        :bla "bla"))

; compiles to
"
{ foo : 'foo',
  bla : 'bla' }
"

```

ParenScript features a HTML generator. Using the same syntax as the HTML-GEN package of Franz, Inc., it can generate JavaScript string expressions. This allows for a clean integration of HTML in ParenScript code, instead of writing the tedious and error-prone string generation code generally found in JavaScript.

```

(ps
  (defun add-div (name href link-text)
    (document.write
      (ps-html ((:div :id name)
                "The link is: "
                ((:a :href href) link-text))))))

; compiles to
"
function addDiv(name, href, linkText) {
  document.write('<div id="' + name + '">The link is: <a href="'
    + href + '">'
    + linkText + '</a></div>');
}
"

```

In order to have a complete web application framework available in Lisp, ParenScript also provides a sexp-based syntax for CSS stylesheets. Thus, a complete web application featuring HTML, CSS and JavaScript documents can be generated using Lisp syntax, allowing the programmer to use Lisp macros to factor out the redundancies and complexities of Web syntax. For example, to generate a CSS inline node in a HTML document using the AllegroServe HTMLGEN library:

```

(html-stream *standard-output*
  (html
    (:html
      (:head
        (css (* :border "1px solid black")
              (div.bl0rg :font-family "serif")
              (("a:active" "a:hoover") :color "black" :size "200%")))))

; which produces

<html><head><style type="text/css">
<!--
* {
  border:1px solid black;
}

div.bl0rg {

```

```

    font-family:serif;
  }

  a:active,a:hoover {
    color:black;
    size:200%;
  }

-->
</style>
</head>
</html>

```

3 ParenScript Tutorial

This chapter is a short introductory tutorial to ParenScript. It hopefully will give you an idea how ParenScript can be used in a Lisp web application.

4 Setting up the ParenScript environment

In this tutorial, we will use the Portable Allegroserve webserver to serve the tutorial web application. We use the ASDF system to load both Allegroserve and ParenScript. I assume you have installed and downloaded Allegroserve and Parenscript, and know how to setup the central registry for ASDF.

```

(asdf:oos 'asdf:load-op :aserve)

; ... lots of compiler output ...

(asdf:oos 'asdf:load-op :parenscrip)

; ... lots of compiler output ...

```

The tutorial will be placed in its own package, which we first have to define.

```

(defpackage :js-tutorial
  (:use :common-lisp :net.aserve :net.html.generator :parenscrip))

(in-package :js-tutorial)

```

The next command starts the webserver on the port 8080.

```

(start :port 8080)

```

We are now ready to generate the first JavaScript-enabled webpages using ParenScript.

5 A simple embedded example

The first document we will generate is a simple HTML document, which features a single hyperlink. When clicking the hyperlink, a JavaScript handler

opens a popup alert window with the string “Hello world”. To facilitate the development, we will factor out the HTML generation to a separate function, and setup a handler for the url “/tutorial1”, which will generate HTTP headers and call the function TUTORIAL1. At first, our function does nothing.

```
(defun tutorial1 (req ent)
  (declare (ignore req ent))
  nil)

(publish :path "/tutorial1"
        :content-type "text/html; charset=ISO-8859-1"
        :function (lambda (req ent)
                    (with-http-response (req ent)
                      (with-http-body (req ent)
                        (tutorial1 req ent))))))
```

Browsing “http://localhost:8080/tutorial1” should return an empty HTML page. It’s now time to fill this rather page with content. ParenScript features a macro that generates a string that can be used as an attribute value of HTML nodes.

```
(defun tutorial1 (req ent)
  (declare (ignore req ent))
  (html
   (:html
    (:head (:title "ParenScript tutorial: 1st example"))
    (:body (:h1 "ParenScript tutorial: 1st example")
           (:p "Please click the link below." :br
              ((:a :href "#" :onclick (ps-inline
                                     (alert "Hello World"))
                 "Hello World"))))))))
```

Browsing “http://localhost:8080/tutorial1” should return the following HTML:

```
<html><head><title>ParenScript tutorial: 1st example</title>
</head>
<body><h1>ParenScript tutorial: 1st example</h1>
<p>Please click the link below.<br/>
<a href="#"
  onclick="javascript:alert(&quot;Hello World&quot;);">Hello World</a>
</p>
</body>
</html>
```

6 Adding an inline ParenScript

Suppose we now want to have a general greeting function. One way to do this is to add the javascript in a SCRIPT element at the top of the HTML page. This is done using the JS-SCRIPT macro (defined below) which will generate the necessary XML and comment tricks to cleanly embed JavaScript. We will redefine our TUTORIAL1 function and add a few links:

```
(defmacro js-script (&rest body)
  "Utility macro for including ParenScript into the HTML notation"
```

```

of net.html.generator library that comes with AllegroServe."
'((:script :type "text/javascript")
  (:princ (format nil "~%// <![CDATA[~%")
    (:princ (ps ,@body))
    (:princ (format nil "~%// ]]>~%")))))

(defun tutorial1 (req ent)
  (declare (ignore req ent))
  (html
    (:html
      (:head
        (:title "ParenScript tutorial: 2nd example")
        (js-script
          (defun greeting-callback ()
            (alert "Hello World"))))
      (:body
        (:h1 "ParenScript tutorial: 2nd example")
        (:p "Please click the link below." :br
          ((:a :href "#" :onclick (ps-inline (greeting-callback)))
            "Hello World")
          :br "And maybe this link too." :br
          ((:a :href "#" :onclick (ps-inline (greeting-callback)))
            "Knock knock")
          :br "And finally a third link." :br
          ((:a :href "#" :onclick (ps-inline (greeting-callback)))
            "Hello there"))))))))

```

This will generate the following HTML page, with the embedded JavaScript nicely sitting on top. Take note how GREETING-CALLBACK was converted to camelcase, and how the lispy DEFUN was converted to a JavaScript function declaration.

```

<html><head><title>ParenScript tutorial: 2nd example</title>
<script type="text/javascript">
// <![CDATA[
function greetingCallback() {
  alert("Hello World");
}
// ]]>
</script>
</head>
<body><h1>ParenScript tutorial: 2nd example</h1>
<p>Please click the link below.<br/>
<a href="#"
  onclick="javascript:greetingCallback();">Hello World</a>
<br/>
And maybe this link too.<br/>
<a href="#"
  onclick="javascript:greetingCallback();">Knock knock</a>
<br/>

And finally a third link.<br/>
<a href="#"
  onclick="javascript:greetingCallback();">Hello there</a>

```

```

    </p>
  </body>
</html>

```

7 Generating a JavaScript file

The best way to integrate ParenScript into a Lisp application is to generate a JavaScript file from ParenScript code. This file can be cached by intermediate proxies, and webbrowsers won't have to reload the JavaScript code on each pageview. We will publish the tutorial JavaScript under `"/tutorial.js"`.

```

(defun tutorial1-file (req ent)
  (declare (ignore req ent))
  (html (:princ
    (ps (defun greeting-callback ()
      (alert "Hello World")))))

(publish :path "/tutorial1.js"
  :content-type "text/javascript; charset=ISO-8859-1"
  :function (lambda (req ent)
    (with-http-response (req ent)
      (with-http-body (req ent)
        (tutorial1-file req ent)))))

(defun tutorial1 (req ent)
  (declare (ignore req ent))
  (html
    (:html
      (:head
        (:title "ParenScript tutorial: 3rd example")
        ((:script :language "JavaScript" :src "/tutorial1.js")))
      (:body
        (:h1 "ParenScript tutorial: 3rd example")
        (:p "Please click the link below." :br
          ((:a :href "#" :onclick (ps-inline (greeting-callback)))
            "Hello World")
          :br "And maybe this link too." :br
          ((:a :href "#" :onclick (ps-inline (greeting-callback)))
            "Knock knock")
          :br "And finally a third link." :br
          ((:a :href "#" :onclick (ps-inline (greeting-callback)))
            "Hello there")))))

```

This will generate the following JavaScript code under `"/tutorial1.js"`:

```

function greetingCallback() {
  alert("Hello World");
}

```

and the following HTML code:

```

<html><head><title>ParenScript tutorial: 3rd example</title>
<script language="JavaScript" src="/tutorial1.js"></script>

```



```

</head>
<body><h1>ParenScript tutorial: 3rd example</h1>
<p>Please click the link below.<br/>
<a href="#" onclick="javascript:greetingCallback();">Hello World</a>
<br/>
And maybe this link too.<br/>
<a href="#" onclick="javascript:greetingCallback();">Knock knock</a>
<br/>

And finally a third link.<br/>
<a href="#" onclick="javascript:greetingCallback();">Hello there</a>
</p>
</body>
</html>

```

8 A ParenScript slideshow

While developing ParenScript, I used JavaScript programs from the web and rewrote them using ParenScript. This is a nice slideshow example from

<http://www.dynamicdrive.com/dynamicindex14/dhtmlslide.htm>

The slideshow will be accessible under “/slideshow”, and will slide through the images “photo1.png”, “photo2.png” and “photo3.png”. The first ParenScript version will be very similar to the original JavaScript code. The second version will then show how to integrate data from the Lisp environment into the ParenScript code, allowing us to customize the slideshow application by supplying a list of image names. We first setup the slideshow path.

```

(publish :path "/slideshow"
  :content-type "text/html"
  :function (lambda (req ent)
    (with-http-response (req ent)
      (with-http-body (req ent)
        (slideshow req ent))))))

(publish :path "/slideshow.js"
  :content-type "text/html"
  :function (lambda (req ent)
    (with-http-response (req ent)
      (with-http-body (req ent)
        (js-slideshow req ent))))))

```

The images are just random files I found on my harddrive. We will publish them by hand for now.

```

(publish-file :path "/photo1.jpg"
  :file "/home/viper/photo1.jpg")
(publish-file :path "/photo2.jpg"
  :file "/home/viper/photo2.jpg")
(publish-file :path "/photo3.jpg"
  :file "/home/viper/photo3.jpg")

```

The function `SLIDESHOW` generates the HTML code for the main slideshow page. It also features little bits of ParenScript. These are the callbacks on the links for the slideshow application. In this special case, the javascript generates the links itself by using `document.write` in a “SCRIPT” element. Users that don’t have JavaScript enabled won’t see anything at all.

`SLIDESHOW` also generates a static array called `PHOTOS` which holds the links to the photos of the slideshow. This array is handled by the ParenScript code in “slideshow.js”. Note how the HTML code issued by ParenScript is generated using the `PS-HTML` construct. In fact, there are two different HTML generators in the example below, one is the AllegroServe HTML generator, and the other is the ParenScript standard library HTML generator, which produces a JavaScript expression which evaluates to an HTML string.

```
(defun slideshow (req ent)
  (declare (ignore req ent))
  (html
    (:html
      (:head (:title "ParenScript slideshow")
        ((:script :language "JavaScript"
          :src "/slideshow.js"))
        (js-script
          (defvar *linkornot* 0)
          (defvar photos (array "photo1.jpg"
                                "photo2.jpg"
                                "photo3.jpg"))))
      (:body (:h1 "ParenScript slideshow")
        (:body (:h2 "Hello")
          ((:table :border 0
            :cellspacing 0
            :cellpadding 0)
            (:tr ((:td :width "100%" :colspan 2 :height 22)
              (:center
                (js-script
                  (let ((img (ps-html
                    ((:img :src (aref photos 0)
                      :name "photoslider"
                      :style (+ "filter:"
                        (lisp (ps (reveal-trans
                          (setf duration 2)
                          (setf transition 23))))))
                    :border 0))))))
                  (document.write
                    (if (= *linkornot* 1)
                      (ps-html ((:a :href "#"
                        :onclick (lisp (ps-inline (transport))))
                        img))
                      img))))))
                  (:tr ((:td :width "50%" :height "21")
                    ((:p :align "left")
                      ((:a :href "#"
                        :onclick (ps-inline (backward)
                          (return false)))
                          "Previous Slide"))
                    ((:td :width "50%" :height "21")
```

```

((:p :align "right")
  ((:a :href "#"
    :onclick (ps-inline (forward)
                        (return false)))
    "Next Slide")))))))

```

SLIDESHOW generates the following HTML code (long lines have been broken):

```

<html><head><title>ParenScript slideshow</title>
<script language="JavaScript" src="/slideshow.js"></script>
<script type="text/javascript">
// <![CDATA[
var LINKORNOT = 0;
var photos = [ "photo1.jpg", "photo2.jpg", "photo3.jpg" ];
// ]]>
</script>
</head>
<body><h1>ParenScript slideshow</h1>
<body><h2>Hello</h2>
<table border="0" cellspacing="0" cellpadding="0">
<tr><td width="100%" colspan="2" height="22">
<center><script type="text/javascript">
// <![CDATA[
var img =
  "<img src=\"\" + photos[0]
  + \"\" name=\"photoslider\"
  style=\"filter:revealTrans(duration=2,transition=23)\"
  border=\"0\"></img>";
document.write(LINKORNOT == 1 ?
  "<a href=\"#\"\"
  onclick=\"javascript:transport()\">\"
  + img + "</a>\"
  : img);
// ]]>
</script>
</center>
</td>
</tr>
<tr><td width="50%" height="21"><p align="left">
<a href="#"
  onclick="javascript:backward(); return false;">Previous Slide</a>

</p>
</td>
<td width="50%" height="21"><p align="right">
<a href="#"
  onclick="javascript:forward(); return false;">Next Slide</a>

</p>
</td>
</tr>
</table>
</body>
</body>
</html>

```

The actual slideshow application is generated by the function `JS-SLIDESHOW`, which generates a ParenScript file. Symbols are converted to JavaScript variables, but the dot “.” is left as is. This enables convenient access to object slots without using the `SLOT-VALUE` function all the time. However, when the object we are referring to is not a variable, but for example an element of an array, we have to revert to `SLOT-VALUE`.

```
(defun js-slideshow (req ent)
  (declare (ignore req ent))
  (html
    (:princ
      (ps
        (defvar *preloaded-images* (make-array))
        (defun preload-images (photos)
          (dotimes (i photos.length)
            (setf (aref *preloaded-images* i) (new *Image)
              (slot-value (aref *preloaded-images* i) 'src)
              (aref photos i))))

        (defun apply-effect ()
          (when (and document.all photoslider.filters)
            (let ((trans photoslider.filters.reveal-trans))
              (setf (slot-value trans '*Transition)
                (floor (* (random) 23)))
              (trans.stop)
              (trans.apply))))

        (defun play-effect ()
          (when (and document.all photoslider.filters)
            (photoslider.filters.reveal-trans.play)))

        (defvar *which* 0)

        (defun keep-track ()
          (setf window.status
            (+ "Image " (1+ *which*) " of " photos.length)))

        (defun backward ()
          (when (> *which* 0)
            (decf *which*)
            (apply-effect)
            (setf document.images.photoslider.src
              (aref photos *which*))
            (play-effect)
            (keep-track)))

        (defun forward ()
          (when (< *which* (1- photos.length))
            (incf *which*)
            (apply-effect)
            (setf document.images.photoslider.src
              (aref photos *which*))
            (play-effect)
            (keep-track)))
```

```
(defun transport ()
  (setf window.location (aref photoslink *which*))))))
```

JS-SLIDESHOW generates the following JavaScript code:

```
var PRELOADEDIMAGES = new Array();
function preloadImages(photos) {
  for (var i = 0; i != photos.length; i = i++) {
    PRELOADEDIMAGES[i] = new Image;
    PRELOADEDIMAGES[i].src = photos[i];
  }
}
function applyEffect() {
  if (document.all && photoslider.filters) {
    var trans = photoslider.filters.revealTrans;
    trans.Transition = Math.floor(Math.random() * 23);
    trans.stop();
    trans.apply();
  }
}
function playEffect() {
  if (document.all && photoslider.filters) {
    photoslider.filters.revealTrans.play();
  }
}
var WHICH = 0;
function keepTrack() {
  window.status = "Image " + (WHICH + 1) + " of " +
    photos.length;
}
function backward() {
  if (WHICH > 0) {
    --WHICH;
    applyEffect();
    document.images.photoslider.src = photos[WHICH];
    playEffect();
    keepTrack();
  }
}
function forward() {
  if (WHICH < photos.length - 1) {
    ++WHICH;
    applyEffect();
    document.images.photoslider.src = photos[WHICH];
    playEffect();
    keepTrack();
  }
}
function transport() {
  window.location = photoslink[WHICH];
}
```

9 Customizing the slideshow

For now, the slideshow has the path to all the slideshow images hardcoded in the HTML code, as well as in the publish statements. We now want to customize this by publishing a slideshow under a certain path, and giving it a list of image urls and pathnames where those images can be found. For this, we will create a function `PUBLISH-SLIDESHOW` which takes a prefix as argument, as well as a list of image pathnames to be published.

```
(defun publish-slideshow (prefix images)
  (let* ((js-url (format nil "~Aslideshow.js" prefix))
        (html-url (format nil "~Aslideshow" prefix))
        (image-urls
         (mapcar (lambda (image)
                   (format nil "~A~A.~A" prefix
                           (pathname-name image)
                           (pathname-type image)))
                  images)))
    (publish :path html-url
            :content-type "text/html"
            :function (lambda (req ent)
                        (with-http-response (req ent)
                          (with-http-body (req ent)
                            (slideshow2 req ent image-urls))))))
    (publish :path js-url
            :content-type "text/html"
            :function (lambda (req ent)
                        (with-http-response (req ent)
                          (with-http-body (req ent)
                            (js-slideshow req ent))))))
    (map nil (lambda (image url)
              (publish-file :path url
                           :file image))
         images image-urls)))

(defun slideshow2 (req ent image-urls)
  (declare (ignore req ent))
  (html
   (:html
    (:head (:title "ParenScript slideshow")
           ((:script :language "JavaScript"
                     :src "/slideshow.js"))
           ((:script :type "text/javascript")
            (:princ (format nil "%// <![CDATA[%")
                     (:princ (ps (defvar *linkornot* 0)))
                     (:princ (ps* '(defvar photos (array ,@image-urls))))
                     (:princ (format nil "%// ]]>%")))))
    (:body (:h1 "ParenScript slideshow")
           (:body (:h2 "Hello")
                  ((:table :border 0
                           :cellspacing 0
                           :cellpadding 0)
                   (:tr ((:td :width "100%" :colspan 2 :height 22)
                        (:center
```

```

(js-script
 (let ((img (ps-html
              ( (:img :src (aref photos 0)
                      :name "photoslider"
                      :style (+ "filter:"
                               (lisp (ps (reveal-trans
                                         (setf duration 2)
                                         (setf transition 23))))))
              :border 0))))))
 (document.write
  (if (= *linkornot* 1)
    (ps-html ((:a :href "#"
                  :onclick (lisp (ps-inline (transport))))
              img))
    img))))))
 (:tr ((:td :width "50%" :height "21")
       ((:p :align "left")
        ((:a :href "#"
              :onclick (ps-inline (backward)
                                  (return false)))
         "Previous Slide"))
       ((:td :width "50%" :height "21")
        ((:p :align "right")
         ((:a :href "#"
               :onclick (ps-inline (forward)
                                   (return false)))
          "Next Slide"))))))))

```

We can now publish the same slideshow as before, under the `"/bknr/"` prefix:

```

(publish-slideshow "/bknr/"
 '("/home/viper/photo1.jpg" "/home/viper/photo2.jpg" "/home/viper/photo3.jpg"))

```

That's it, we can now access our customized slideshow under

```

http://localhost:8080/bknr/slideshow

```

10 ParenScript Language Reference

This chapter describes the core constructs of ParenScript, as well as its compilation model. This chapter is aimed to be a comprehensive reference for ParenScript developers. Programmers looking for how to tweak the ParenScript compiler itself should turn to the ParenScript Internals chapter.

11 Statements and Expressions

In contrast to Lisp, where everything is an expression, JavaScript makes the difference between an expression, which evaluates to a value, and a statement, which has no value. Examples for JavaScript statements are `for`, `with` and `while`. Most ParenScript forms are expression, but certain special forms are not (the forms which are transformed to a JavaScript statement). All ParenScript expressions are statements though. Certain forms, like `IF` and `PROGN`,

generate different JavaScript constructs whether they are used in an expression context or a statement context. For example:

```
(+ i (if 1 2 3)) => i + (1 ? 2 : 3)

(if 1 2 3)
=> if (1) {
  2;
} else {
  3;
}
```

12 Symbol conversion

Lisp symbols are converted to JavaScript symbols by following a few simple rules. Special characters `!`, `?`, `#`, `@`, `%`, `'`, `/`, `*` and `+` get replaced by their written-out equivalents “bang”, “what”, “hash”, “at”, “percent”, “slash”, “start” and “plus” respectively. The `$` character is untouched.

```
! ? # @ % => bangwhathashatpercent
```

The `-` is an indication that the following character should be converted to uppercase. Thus, `-` separated symbols are converted to camelcase. The `_` character however is left untouched.

```
bla-foo-bar => blaFooBar
```

If you want a JavaScript symbol beginning with an uppercase, you can either use a leading `-`, which can be misleading in a mathematical context, or a leading `*`.

```
*array => Array
```

The `.` character is left as is in symbols. This allows the ParenScript programmer to use a practical shortcut when accessing slots or methods of JavaScript objects. Instead of writing

```
(slot-value foobar 'slot)
```

we can write

```
foobar.slot
```

A symbol beginning and ending with `+` or `*` is converted to all uppercase, to signify that this is a constant or a global variable.

```
*global-array*      => GLOBALARRAY
*global-array*.length => GLOBALARRAY.length
```


12.1 Reserved Keywords

The following keywords and symbols are reserved in ParenScript, and should not be used as variable names.

```
! ~ ++ -- * / % + - << >> >>> < > <= >= == != ===== != & ^ | && ||
*= /= %= += -= <=> >>=> &= ^= |= 1- 1+
ABSTRACT AND AREF ARRAY BOOLEAN BREAK BYTE CASE CATCH CC-IF CHAR CLASS
COMMA CONST CONTINUE CREATE DEBUGGER DECF DEFAULT DEFUN DEFVAR DELETE
DO DOEACH DOLIST DOTIMES DOUBLE ELSE ENUM EQL EXPORT EXTENDS FALSE
FINAL FINALLY FLOAT FLOOR FOR FUNCTION GOTO IF IMPLEMENTS IMPORT IN INCF
INSTANCEOF INT INTERFACE JS LAMBDA LET LISP LIST LONG MAKE-ARRAY NATIVE NEW
NIL NOT OR PACKAGE PRIVATE PROGN PROTECTED PUBLIC RANDOM REGEX RETURN
SETF SHORT SLOT-VALUE STATIC SUPER SWITCH SYMBOL-MACROLET SYNCHRONIZED T
THIS THROW THROWS TRANSIENT TRY TYPEOF UNDEFINED UNLESS VAR VOID VOLATILE
WHEN WHILE WITH WITH-SLOTS
```

13 Literal values

13.1 Number literals

```
; number ::= a Lisp number
```

ParenScript supports the standard JavaScript literal values. Numbers are compiled into JavaScript numbers.

```
1          => 1
123.123    => 123.123
```

Note that the base is not conserved between Lisp and JavaScript.

```
#x10       => 16
```

13.2 String literals

```
; string ::= a Lisp string
```

Lisp strings are converted into JavaScript literals.

```
"foobar"    => 'foobar'
"bratzel bub" => 'bratzel bub'
```

Escapes in Lisp are not converted to JavaScript escapes. However, to avoid having to use double backslashes when constructing a string, you can use the CL-INTERPOL library by Edi Weitz.

13.3 Array literals

```
; (ARRAY {values}*)
; (MAKE-ARRAY {values}*)
; (AREF array index)
;
; values ::= a ParenScript expression
; array  ::= a ParenScript expression
; index  ::= a ParenScript expression
```

Array literals can be created using the `ARRAY` form.

```
(array)          => [ ]

(array 1 2 3) => [ 1, 2, 3 ]

(array (array 2 3)
      (array "foobar" "bratzel bub"))
=> [ [ 2, 3 ], [ 'foobar', 'bratzel bub' ] ]
```

Arrays can also be created with a call to the `Array` function using the `MAKE-ARRAY`. The two forms have the exact same semantic on the JavaScript side.

```
(make-array)          => new Array()

(make-array 1 2 3) => new Array(1, 2, 3)

(make-array
 (make-array 2 3)
 (make-array "foobar" "bratzel bub"))
=> new Array(new Array(2, 3), new Array('foobar', 'bratzel bub'))
```

Indexing arrays in ParenScript is done using the form `AREF`. Note that JavaScript knows of no such thing as an array. Subscripting an array is in fact reading a property from an object. So in a semantic sense, there is no real difference between `AREF` and `SLOT-VALUE`.

13.4 Object literals

```
; (CREATE {name value}*)
; (SLOT-VALUE object slot-name)
; (WITH-SLOTS ({slot-name}*) object body)
;
; name      ::= a ParenScript symbol or a Lisp keyword
; value     ::= a ParenScript expression
; object    ::= a ParenScript object expression
; slot-name ::= a quoted Lisp symbol
; body      ::= a list of ParenScript statements
```

Object literals can be created using the `CREATE` form. Arguments to the `CREATE` form is a list of property names and values. To be more “lisp-y”, the property names can be keywords.

```

(create :foo "bar" :blorg 1)
=> { foo : 'bar',
    blorg : 1 }

(create :foo "hihi"
      :blorg (array 1 2 3)
      :another-object (create :schtrunz 1))
=> { foo : 'hihi',
    blorg : [ 1, 2, 3 ],
    anotherObject : { schtrunz : 1 } }

```

Object properties can be accessed using the `SLOT-VALUE` form, which takes an object and a slot-name.

```

(slot-value an-object 'foo) => anObject.foo

```

A programmer can also use the `"."` symbol notation explained above.

```

an-object.foo => anObject.foo

```

The form `WITH-SLOTS` can be used to bind the given slot-name symbols to a macro that will expand into a `SLOT-VALUE` form at expansion time.

```

(with-slots (a b c) this
  (+ a b c))
=> this.a + this.b + this.c;

```

13.5 Regular Expression literals

```

; (REGEX regex)
;
; regex ::= a Lisp string

```

Regular expressions can be created by using the `REGEX` form. If the argument does not start with a slash, it is surrounded by slashes to make it a proper JavaScript regex. If the argument starts with a slash it is left as it is. This makes it possible to use modifiers such as `slash-i` (case-insensitive) or `slash-g` (match-globally (all)).

```

(regex "foobar") => /foobar/

(regex "/foobar/i") => /foobar/i

```

Here `CL-INTERPOL` proves really useful.

```

(regex #?r"/([^\s]+)foobar/i") => /([^\s]+)foobar/i

```

13.6 Literal symbols

```

; T, FALSE, NIL, UNDEFINED, THIS

```

The Lisp symbols `T` and `FALSE` are converted to their JavaScript boolean equivalents `true` and `false`.

```
T      => true
FALSE => false
```

The Lisp symbol `NIL` is converted to the JavaScript keyword `null`.

```
NIL => null
```

The Lisp symbol `UNDEFINED` is converted to the JavaScript keyword `undefined`.

```
UNDEFINED => undefined
```

The Lisp symbol `THIS` is converted to the JavaScript keyword `this`.

```
THIS => this
```

14 Variables

```
; variable ::= a Lisp symbol
```

All the other literal Lisp values that are not recognized as special forms or symbol macros are converted to JavaScript variables. This extreme freedom is actually quite useful, as it allows the ParenScript programmer to be flexible, as flexible as JavaScript itself.

```
variable      => variable
a-variable    => aVariable
*math         => Math
*math.floor   => Math.floor
```

15 Function calls and method calls

```
; (function {argument}*)
; (method  object {argument}*)
;
; function ::= a ParenScript expression or a Lisp symbol
; method   ::= a Lisp symbol beginning with .
; object   ::= a ParenScript expression
; argument ::= a ParenScript expression
```

Any list passed to the JavaScript that is not recognized as a macro or a special form (see “Macro Expansion” below) is interpreted as a function call. The function call is converted to the normal JavaScript function call representation, with the arguments given in paren after the function name.

```
(blorg 1 2) => blorg(1, 2)

(foo (blorg 1 2) (blabla 3 4) (array 2 3 4))
=> foo(blorg(1, 2), blabla(3, 4), [ 2, 3, 4 ])

((aref foo i) 1 2) => foo[i](1, 2)
```

A method call is a function call where the function name is a symbol and begins with a `."`. In a method call, the name of the function is append to its first argument, thus reflecting the method call syntax of JavaScript. Please note that most method calls can be abbreviated using the `."` trick in symbol names (see "Symbol Conversion" above).

```
(.blorg this 1 2) => this.blorg(1, 2)

(this.blorg 1 2) => this.blorg(1, 2)

(.blorg (aref foobar 1) NIL T)
=> foobar[1].blorg(null, true)
```

16 Operator Expressions

```
; (operator {argument}*)
; (single-operator argument)
;
; operator ::= one of *, /, %, +, -, <<, >>, >>>, < >, EQL,
;               ==, !=, =, ===, !==, &, ^, |, &&, AND, ||, OR.
; single-operator ::= one of INCF, DECF, ++, --, NOT, !
; argument ::= a ParenScript expression
```

Operator forms are similar to function call forms, but have an operator as function name.

Please note that `=` is converted to `==` in JavaScript. The `=` ParenScript operator is not the assignment operator. Unlike JavaScript, ParenScript supports multiple arguments to the operators.

```
(* 1 2)    => 1 * 2

(= 1 2)     => 1 == 2

(eql 1 2)   => 1 == 2
```

Note that the resulting expression is correctly parenthesized, according to the JavaScript operator precedence that can be found in table form at:

```
http://www.codehouse.com/javascript/precedence/

(* 1 (+ 2 3 4) 4 (/ 6 7))
=> 1 * (2 + 3 + 4) * 4 * (6 / 7)
```

The pre increment and decrement operators are also available. `INCF` and `DECF` are the pre-incrementing and pre-decrementing operators. These operators can take only one argument.

```
(incf i) => ++i

(decf i) => --i
```

The `1+` and `1-` operators are shortcuts for adding and subtracting 1.

```
(1- i) => i - 1

(1+ i) => i + 1
```

The `not` operator actually optimizes the code a bit. If `not` is used on another boolean-returning operator, the operator is reversed.

```
(not (< i 2)) => i >= 2

(not (eql i 2)) => i != 2
```

17 Body forms

```
; (PROGN {statement}*) in statement context
; (PROGN {expression}*) in expression context
;
; statement ::= a ParenScript statement
; expression ::= a ParenScript expression
```

The `PROGN` special form defines a sequence of statements when used in a statement context, or sequence of expression when used in an expression context. The `PROGN` special form is added implicitly around the branches of conditional executions forms, function declarations and iteration constructs. For example, in a statement context:

```
(progn (blorg i) (blafoo i))
=> blorg(i);
    blafoo(i);
```

In an expression context:

```
(+ i (progn (blorg i) (blafoo i)))
=> i + (blorg(i), blafoo(i))
```

A `PROGN` form doesn't lead to additional indentation or additional braces around it's body.

18 Function Definition

```
; (DEFUN name ({argument}*) body)
; (LAMBDA ({argument}*) body)
;
; name      ::= a Lisp Symbol
; argument  ::= a Lisp symbol
; body      ::= a list of ParenScript statements
```

As in Lisp, functions are defined using the `DEFUN` form, which takes a name, a list of arguments, and a function body. An implicit `PROGN` is added around the body statements.

```

(defun a-function (a b)
  (return (+ a b)))
=> function aFunction(a, b) {
    return a + b;
  }

```

Anonymous functions can be created using the `LAMBDA` form, which is the same as `DEFUN`, but without function name. In fact, `LAMBDA` creates a `DEFUN` with an empty function name.

```

(lambda (a b) (return (+ a b)))
=> function (a, b) {
    return a + b;
  }

```

19 Assignment

```

; (SETF {lhs rhs}*)
;
; lhs ::= a ParenScript left hand side expression
; rhs ::= a ParenScript expression

```

Assignment is done using the `SETF` form, which is transformed into a series of assignments using the JavaScript `=` operator.

```

(setf a 1) => a = 1;

(setf a 2 b 3 c 4 x (+ a b c))
=> a = 2;
   b = 3;
   c = 4;
   x = a + b + c;

```

The `SETF` form can transform assignments of a variable with an operator expression using this variable into a more “efficient” assignment operator form. For example:

```

(setf a (1+ a))      => a++;

(setf a (+ a 2 3 4 a)) => a += 2 + 3 + 4 + a;

(setf a (- 1 a))     => a = 1 - a;

```

New types of `setf` places can be defined in one of two ways: using `DEFSETF` or using `DEFUN` with a `setf` function name; both are analogous to their Common Lisp counterparts. `DEFSETF` supports both long and short forms, while `DEFUN` of a `setf` place generates a JavaScript function name with the `__setf_` prefix:

```

(defun (setf color) (new-color el)
  (setf (slot-value (slot-value el 'style) 'color) new-color))
=> function __setf_color(newColor, el) {
    el.style.color = newColor;
  };

```

```
(setf (color some-div) (+ 23 "em"))
=> var _js2 = someDiv;
    var _js1 = 23 + 'em';
    __setf_color(_js1, _js2);
```

Note that temporary variables are generated to preserve evaluation order of the arguments as they would be in Lisp. The following example illustrates how setf places can be used to provide a uniform protocol for positioning elements in HTML pages:

```
(defsetf left (el) (offset)
  '(setf (slot-value (slot-value ,el 'style) 'left) ,offset)) => null

(setf (left some-div) (+ 123 "px"))
=> var _js2 = someDiv;
    var _js1 = 123 + 'px';
    _js2.style.left = _js1;

(progn (defmacro left (el)
  '(slot-value ,el 'offset-left))
  (left some-div))
=> someDiv.offsetLeft;
```

20 Single argument statements

```
; (RETURN {value}?)
; (THROW {value}?)
;
; value ::= a ParenScript expression
```

The single argument statements `return` and `throw` are generated by the form `RETURN` and `THROW`. `THROW` has to be used inside a `TRY` form. `RETURN` is used to return a value from a function call.

```
(return 1)      => return 1

(throw "foobar") => throw 'foobar'
```

21 Single argument expression

```
; (DELETE {value})
; (VOID {value})
; (TYPEOF {value})
; (INSTANCEOF {value})
; (NEW {value})
;
; value ::= a ParenScript expression
```

The single argument expressions `delete`, `void`, `typeof`, `instanceof` and `new` are generated by the forms `DELETE`, `VOID`, `TYPEOF`, `INSTANCEOF` and `NEW`. They all take a `ParenScript` expression.


```

(delete (new (*foobar 2 3 4))) => delete new Foobar(2, 3, 4)

(if (= (typeof blorg) *string)
    (alert (+ "blorg is a string: " blorg))
    (alert "blorg is not a string"))
=> if (typeof blorg == String) {
    alert('blorg is a string: ' + blorg);
  } else {
    alert('blorg is not a string');
  }

```

22 Conditional Statements

```

; (IF conditional then {else})
; (WHEN condition then)
; (UNLESS condition then)
;
; condition ::= a ParenScript expression
; then      ::= a ParenScript statement in statement context, a
;              ParenScript expression in expression context
; else      ::= a ParenScript statement in statement context, a
;              ParenScript expression in expression context

```

The `IF` form compiles to the `if` javascript construct. An explicit `PROGN` around the then branch and the else branch is needed if they consist of more than one statement. When the `IF` form is used in an expression context, a JavaScript `?`, `:` operator form is generated.

```

(if (blorg.is-correct)
    (progn (carry-on) (return i))
    (alert "blorg is not correct!"))
=> if (blorg.isCorrect()) {
    carryOn();
    return i;
  } else {
    alert('blorg is not correct!');
  }

(+ i (if (blorg.add-one) 1 2))
=> i + (blorg.addOne() ? 1 : 2)

```

The `WHEN` and `UNLESS` forms can be used as shortcuts for the `IF` form.

```

(when (blorg.is-correct)
    (carry-on)
    (return i))
=> if (blorg.isCorrect()) {
    carryOn();
    return i;
  }

(unless (blorg.is-correct)
    (alert "blorg is not correct!"))

```

```
=> if (!blorg.isCorrect()) {
    alert('blorg is not correct!');
}
```

23 Variable declaration

```
; (DEFVAR var {value}?)
; (LET ({var | (var value)} body)
;
; var    ::= a Lisp symbol
; value ::= a ParenScript expression
; body  ::= a list of ParenScript statements
```

Variables (either local or global) can be declared using the `DEFVAR` form, which is similar to its equivalent form in Lisp. The `DEFVAR` is converted to “`var ... = ...`” form in JavaScript.

```
(defvar *a* (array 1 2 3)) => var A = [ 1, 2, 3 ]

(if (= i 1)
  (progn (defvar blorg "hallo")
         (alert blorg))
  (progn (defvar blorg "blitzel")
         (alert blorg)))
=> if (i == 1) {
    var blorg = 'hallo';
    alert(blorg);
  } else {
    var blorg = 'blitzel';
    alert(blorg);
  }
```

Another way to declare local variables is to use the `LET` form. Note that the ParenScript `LET` compiles to a straightforward assignment and does not have lexical-scoping semantics, unlike its Lisp cousin.

```
(if (= i 1)
  (let ((blorg "hallo"))
    (alert blorg))
  (let ((blorg "blitzel"))
    (alert blorg)))
=> if (i == 1) {
    var blorg = 'hallo';
    alert(blorg);
  } else {
    var blorg = 'blitzel';
    alert(blorg);
  }
```

Moreover, beware that scoping in Lisp and JavaScript are quite different. For example, don't rely on closures capturing local variables in the way you'd think they would.

24 Iteration constructs

```
; (DO ({var | (var {init}? {step}?)})*) (end-test) body)
; (DOTIMES (var numeric-form) body)
; (DOLIST (var list-form) body)
; (DOEACH (var object) body)
; (WHILE end-test body)
;
; var          ::= a Lisp symbol
; numeric-form ::= a ParenScript expression resulting in a number
; list-form    ::= a ParenScript expression resulting in an array
; object       ::= a ParenScript expression resulting in an object
; init         ::= a ParenScript expression
; step         ::= a ParenScript expression
; end-test     ::= a ParenScript expression
; body        ::= a list of ParenScript statements
```

The `DO` form, which is similar to its Lisp form, is transformed into a JavaScript `for` statement. Note that the ParenScript `DO` form does not have a return value, that is because `for` is a statement and not an expression in JavaScript.

```
(do ((i 0 (1+ i))
     (l (aref blorg i) (aref blorg i)))
    ((or (= i blorg.length)
         (eq l "Fumitastic"))
     (document.write (+ "L is " l)))
=> for (var i = 0, l = blorg[i];
       !(i == blorg.length || l == 'Fumitastic');
       i = i + 1, l = blorg[i]) {
    document.write('L is ' + l);
}
```

The `DOTIMES` form, which lets a variable iterate from 0 upto an end value, is a shortcut for `DO`.

```
(dotimes (i blorg.length)
  (document.write (+ "L is " (aref blorg i))))
=> for (var i = 0; i < blorg.length; i = i + 1) {
    document.write('L is ' + blorg[i]);
}
```

The `DOLIST` form is a shortcut for iterating over an array. Note that this form creates temporary variables using a function called `PS-GENSYM`, which is similar to its Lisp counterpart `GENSYM`.

```
(dolist (l blorg)
  (document.write (+ "L is " l)))
=> var tmpArr1 = blorg;
   for (var tmpI2 = 0; tmpI2 < tmpArr1.length;
        tmpI2 = tmpI2 + 1) {
     var l = tmpArr1[tmpI2];
     document.write('L is ' + l);
  };
```

The `DOEACH` form is converted to a `for (var ... in ...)` form in JavaScript. It is used to iterate over the enumerable properties of an object.

```
(doeach (i object)
  (document.write (+ i " is " (aref object i))))
=> for (var i in object) {
  document.write(i + ' is ' + object[i]);
}
```

The `WHILE` form is transformed to the JavaScript form `while`, and loops until a termination test evaluates to false.

```
(while (film.is-not-finished)
  (this.eat (new *popcorn)))
=> while (film.isNotFinished()) {
  this.eat(new Popcorn);
}
```

25 The 'CASE' statement

```
; (CASE case-value clause*)
;
; clause      ::= (value body) | ((value*) body) | t-clause
; case-value ::= a ParenScript expression
; value       ::= a ParenScript expression
; t-clause    ::= {t | otherwise | default} body
; body        ::= a list of ParenScript statements
```

The Lisp `CASE` form is transformed to a `switch` statement in JavaScript. Note that `CASE` is not an expression in ParenScript.

```
(case (aref blorg i)
  ((1 "one") (alert "one"))
  (2 (alert "two"))
  (t (alert "default clause")))
=> switch (blorg[i]) {
  case 1:
  case 'one':
    alert('one');
    break;
  case 2:
    alert('two');
    break;
  default: alert('default clause');
}

; (SWITCH case-value clause*)
; clause      ::= (value body) | (default body)
```

The `SWITCH` form is the equivalent to a javascript switch statement. No break statements are inserted, and the default case is named `DEFAULT`. The `CASE` form should be preferred in most cases.

```

    (switch (aref blorg i)
      (1 (alert "If I get here"))
      (2 (alert "I also get here"))
      (default (alert "I always get here")))
    => switch (blorg[i]) {
      case 1: alert('If I get here');
      case 2: alert('I also get here');
      default: alert('I always get here');
    }

```

26 The 'WITH' statement

```

; (WITH object body)
;
; object ::= a ParenScript expression evaluating to an object
; body   ::= a list of ParenScript statements

```

The `WITH` form is compiled to a JavaScript `with` statements, and adds the object `object` as an intermediary scope objects when executing the body.

```

(with (create :foo "foo" :i "i")
  (alert (+ "i is now intermediary scoped: " i)))
=> with ({ foo : 'foo',
         i : 'i' }) {
  alert('i is now intermediary scoped: ' + i);
}

```

27 The 'TRY' statement

```

; (TRY body {(:CATCH (var) body)}? {(:FINALLY body)}?)
;
; body ::= a list of ParenScript statements
; var  ::= a Lisp symbol

```

The `TRY` form is converted to a JavaScript `try` statement, and can be used to catch expressions thrown by the `THROW` form. The body of the catch clause is invoked when an exception is caught, and the body of the finally is always invoked when leaving the body of the `TRY` form.

```

(try (throw "i")
  (:catch (error)
    (alert (+ "an error happened: " error))))
(:finally
  (alert "Leaving the try form")))
=> try {
  throw 'i';
} catch (error) {
  alert('an error happened: ' + error);
} finally {
  alert('Leaving the try form');
}

```

28 The HTML Generator

```
| ; (PS-HTML html-expression)
```

The HTML generator of ParenScript is very similar to the `htmlgen` HTML generator library included with AllegroServe. It accepts the same input forms as the AllegroServer HTML generator. However, non-HTML constructs are compiled to JavaScript by the ParenScript compiler. The resulting expression is a JavaScript expression.

```
| (ps-html ((:a :href "foobar") "blorg"))
=> '<a href=\"foobar\">blorg</a>'

(ps-html ((:a :href (generate-a-link)) "blorg"))
=> '<a href=\"' + generateALink() + '\">blorg</a>'
```

We can recursively call the ParenScript compiler in an HTML expression.

```
| (document.write
  (ps-html ((:a :href "#"
    :onclick (lisp (ps-inline (transport)))) "link")))
=> document.write('<a href=\"#\" onclick=\"' + 'javascript:transport()' + '\">link</a>')
```

Forms may be used in attribute lists to conditionally generate the next attribute. In this example the `textarea` is sometimes disabled.

```
| (let ((disabled nil)
      (authorized t))
  (setf element.inner-h-t-m-l
    (ps-html ((:textarea (or disabled (not authorized)) :disabled "disabled")
      "Edit me"))))
=> var disabled = null;
var authorized = true;
element.innerHTML =
'<textarea'
+ (disabled || !authorized ? ' disabled=\"' + 'disabled' + '\" : '')
+ '>Edit me</textarea>';

; (CSS-INLINE css-expression)
```

Stylesheets can also be created in ParenScript.

```
| (css-inline :color "red"
  :font-size "x-small")
=> 'color:red;font-size:x-small'

(defun make-color-div(color-name)
  (return (ps-html ((:div :style (css-inline :color color-name))
    color-name " looks like this."))))
=> function makeColorDiv(colorName) {
  return '<div style=\"' + ('color:' + colorName) + '\">' + colorName
    + ' looks like this.</div>';
}
```

29 Macrology

```
; (DEFPSMACRO name lambda-list macro-body)
; (MACROLET ({name lambda-list macro-body}*) body)
; (SYMBOL-MACROLET ({name macro-body}*) body)
; (PS-GENSYM {string})
;
; name      ::= a Lisp symbol
; lambda-list ::= a lambda list
; macro-body ::= a Lisp body evaluating to ParenScript code
; body      ::= a list of ParenScript statements
; string    ::= a string
```

ParenScript can be extended using macros, just like Lisp can be extended using Lisp macros. Using the special Lisp form `DEFPSMACRO`, the ParenScript language can be extended. `DEFPSMACRO` adds the new macro to the toplevel macro environment, which is always accessible during ParenScript compilation. For example, the `1+` and `1-` operators are implemented using macros.

```
(defpsmacro 1- (form)
  '(- ,form 1))

(defpsmacro 1+ (form)
  '(+ ,form 1))
```

A more complicated ParenScript macro example is the implementation of the `DOLIST` form (note how `PS-GENSYM`, the ParenScript of `GENSYM`, is used to generate new ParenScript variable names):

```
(defpsmacro dolist (i-array &rest body)
  (let ((var (first i-array))
        (array (second i-array))
        (arrvar (ps-gensym "arr"))
        (idx (ps-gensym "i")))
    '(let ((,arrvar ,array)
          (do ((,idx 0 (incf ,idx))
              ((>= ,idx (slot-value ,arrvar 'length))))
          (let ((,var (aref ,arrvar ,idx)))
            ,@body))))))
```

Macros can be defined in ParenScript code itself (as opposed to from Lisp) by using the ParenScript `MACROLET` and `DEFMACRO` forms. ParenScript also supports the use of macros defined in the underlying Lisp environment. Existing Lisp macros can be imported into the ParenScript macro environment by `IMPORT-MACROS-FROM-LISP`. This functionality enables code sharing between ParenScript and Lisp, and is useful in debugging since the full power of Lisp macroexpanders, editors and other supporting facilities can be used. However, it is important to note that the macroexpansion of Lisp macros and ParenScript macros takes place in their own respective environments, and many Lisp macros (especially those provided by the Lisp implementation) expand into code that is not usable by ParenScript. To make it easy for users to take advantage of these features, two additional macro definition facilities are provided by ParenScript: `DEFMACRO/PS` and `DEFMACRO+PS`. `DEFMACRO/PS` de-

defines a Lisp macro and then imports it into the ParenScript macro environment, while `DEFMACRO+PS` defines two macros with the same name and expansion, one in ParenScript and one in Lisp. `DEFMACRO+PS` is used when the full ‘macroexpand’ of the Lisp macro yields code that cannot be used by ParenScript. ParenScript also supports symbol macros, which can be introduced using the ParenScript form `SYMBOL-MACROLET`. For example, the ParenScript `WITH-SLOTS` is implemented using symbol macros.

```
(defjsmacro with-slots (slots object &rest body)
  '(symbol-macrolet ,(mapcar #'(lambda (slot)
                                '(',slot '(slot-value ,object ',slot)))
                    slots)
    ,@body))
```

30 The ParenScript namespace system

```
; (setf (PS-PACKAGE-PREFIX package-designator) string)
```

Although JavaScript does not offer namespaces or a package system, ParenScript does provide a namespace mechanism for generated JavaScript by integrating with the Common Lisp package system. Since ParenScript code is normally read in by the Lisp reader, all symbols (except for uninterned ones, ie - those specified with the `#:` reader macro) have a Lisp package. By default, no packages are prefixed. You can specify that symbols in a particular package receive a prefix when translated to JavaScript with the `PS-PACKAGE-PREFIX` place.

```
(defpackage "MY-LIBRARY"
  (:use #:parenscrip))
(setf (ps-package-prefix :my-library) "my_library_")

(defun my-library::library-function (x y)
  (return (+ x y)))
-> function my_library_libraryFunction(x, y) {
    return x + y;
  }
```

31 Identifier obfuscation

```
; (OBFUSCATE-PACKAGE package-designator)
; (UNOBFUSCATE-PACKAGE package-designator)
```

Similar to the namespace mechanism, ParenScript provides a facility to generate obfuscated identifiers in certain Lisp packages.

```
(defpackage "OBFUSCATE-ME")
(obfuscate-package :obfuscate-me)

(defun obfuscate-me::library-function2 (a b obfuscate-me::foo)
  (+ a (my-library::library-function b obfuscate-me::foo)))
```

The obfuscation and namespace facilities can be used on packages at the same time.

32 The ParenScript Compiler

```
; (COMPILE-SCRIPT script-form &key (output-stream nil))  
; (PS &body body)  
; (PS* &body body)  
; (PS-INLINE &body body)  
; (LISP &body lisp-forms)  
;  
; body ::= ParenScript statements comprising an implicit 'PROGN'
```

For static ParenScript code, the macros `PS` and `PS-INLINE`, avoid the need to quote the ParenScript expression. `PS*` and `COMPILE-SCRIPT` evaluate their arguments. All these forms except for `COMPILE-SCRIPT` treat the given forms as an implicit `PROGN`. `PS` and `PS*` return a string of the compiled body, while `COMPILE-SCRIPT` takes an optional output-stream parameter that can be used to specify a stream to which the generated JavaScript will be written. `PS-INLINE` generates a string that can be used in HTML node attributes. ParenScript can also call out to arbitrary Lisp code at compile-time using the special form `LISP`. This is typically used to insert the values of Lisp special variables into ParenScript code at compile-time, and can also be used to make nested calls to the ParenScript compiler, which comes in useful when you want to use the result of `PS-INLINE` in `PS-HTML` forms, for example. Alternatively the same thing can be accomplished by constructing ParenScript programs as lists and passing them to `PS*` or `COMPILE-SCRIPT`.